



BUILT FOR
THE WAY
YOU MOVE

Zhejiang Yongtu Power Technology Co., Ltd.
Zhejiang Green Mantis Motorcycle Technology Co., Ltd.

Contact Us

Tel: +86 133 0589 5588 (CEO)

+86 180 0579 9510 (Sales Executive_Fang)

+86 180 0579 9506 (Sales Executive_Guo)

Email: yonttul@163.com

Website: <https://www.ytpowersport.com>

Address: Building 2, No. 878, Kangji North Street, Dongxiao Subdistrict, Jindong District,
Jinhua City, Zhejiang Province, China

DISCOVER MORE



WeChat QR Code



PRODUCT CATALOGUE

2026



COMPANY PROFILE

Zhejiang Yongtu Power Technology Co., Ltd., based in Jinhua, Zhejiang, develops and manufactures gasoline-powered and new-energy vehicles. Its range includes ATVs, UTVs, electric dirt bikes, electric motorcycles, and multi-purpose two- and four-wheel vehicles for recreation, work, and daily travel. Production covers component sourcing, frame fabrication, assembly, and final inspection. Before mass production, new models undergo thousands of kilometres of standardized testing. Together, its Jinhua base and Zhejiang Green Mantis Motorcycle Technology Co., Ltd.'s Yongkang base operate approximately 92,000 m² of manufacturing facilities, with annual capacity for 50,000 premium intelligent ATVs and UTVs and 500,000 premium intelligent motorcycles.



HOW WE BUILD WITH YOU



VEHICLE ENGINEERING

More than 150 engineers develop engines, powertrains and complete vehicles, from concept and prototypes through validation and testing. The T300 and T800-EV ATVs have obtained EU T3 approval, while several electric motorcycle models hold U.S. and EU certifications.



DESIGN & CUSTOMIZATION

For OEM and ODM projects, we tailor vehicle appearance and specifications to target markets, including colours, branding, powertrains, suspension, tyres and equipment. Our design and engineering teams assess each option for practical use and mass production.



LOOKING AHEAD

Yongtu Power and Green Mantis Motorcycle focus on intelligent ATVs and premium electric motorcycles. In China, their vehicles serve emergency response, public-security patrols, and forestry and grassland management. Overseas, they support recreation, farming, forestry and coastal leisure. The companies bring 16 years of independent R&D and dozens of core invention patents to a growing market for intelligent and electric ATVs.



T800-EV

30 kW PEAK POWER

2WD OR 4WD

T800-EV		
VEHICLE	Weight (kg):	Curb: 400 / Gross: 460
	Dimensions (mm):	2085 × 1180 × 1175
	Packing Dimensions (mm):	2250 × 1160 × 1130
	Ground Clearance (mm):	252
	Wheelbase (mm):	1300
	Braking System:	Hydraulic Disc Brake(s)
POWER	Shock:	Hydraulic (F&R)
	Battery:	72 V / 150 Ah or 72 V / 180 Ah
	Charger Specifications:	EU Std 25 A
	Max. Speed (km/h):	L: 45, H: 95
	Range (km):	80 (at 45 km/h)
	Rated Power:	15 kW
	Max. Power:	30 kW
	Controller Specifications:	72 V 450 A
	Dashboard:	LCD Display
OTHERS	USB Port:	5 V 2 A output
	Gear Selection:	H / L / N / R
	Drive Mode:	2WD / 4WD
	Lighting:	12 V LED
	Front Tire:	AT25×8-12 tubeless
	Rear Tire:	AT25×10-12 tubeless
	Loading Quantity (40' HQ):	20 units



T650
585.3 cc

T650
49.5 N·m

T525
493 cc

T525
38.8 N·m



T650 & T525

750 kg TOWING TWO ENGINE CHOICES

	T650	T525
VEHICLE	Weight (kg):	Curb: 420 / Gross: 490
	Dimensions (mm):	2395 × 1305 × 1330
	Ground Clearance (mm):	270
	Wheelbase (mm):	1470
	Fuel Tank Capacity (L):	20
	Braking System:	Hydraulic Disc Brake(s)
	Suspension:	Hydraulic (F&R)
	Max. Speed (km/h):	95
POWER	Displacement:	585.3 cc
	Engine Type:	Single Cylinder, Water-Cooled, 4 Stroke
	Bore × Stroke (mm):	91 × 90
	Max. Power:	31 kW @ 6,700–6,900 rpm
	Max. Torque:	49.5 N·m @ 5,400 rpm
	Compression Ratio:	10.68:1
	Fuel System:	EFI
	Start Type:	Electric starting
OTHERS	Winch:	2,000 lbs
	Gear Selection:	L / H / N / R / P
	Drive Mode:	2WD / 4WD
	Max. Towing Capacity:	750 kg
	Front Tire:	Front: AT25×8-12
	Rear Tire:	Rear: AT25×10-12
	Loading Quantity (40' HQ):	20 units



T550 & T450

500 kg TOWING
TWO ENGINE CHOICES

	T550	T450
VEHICLE	Weight (kg):	Curb: 375 / Gross: 395
	Dimensions (mm):	2090 × 1210 × 1170
	Packing Dimensions (mm):	1970 × 1140 × 880
	Ground Clearance (mm):	310
	Wheelbase (mm):	1360
	Fuel Tank Capacity (L):	20
	Braking System:	Hydraulic Disc Brake(s)
	Shock:	Hydraulic (F&R)
	Max. Speed (km/h):	95
POWER	Engine Type:	Single Cylinder, Water-Cooled
	Displacement (cc):	499.5
	Max. Power:	29 kW @ 6,700–6,900 rpm
	Max. Torque:	46.5 N·m @ 5,750 rpm
	Compression Ratio:	10.3:1
	Bore × Stroke (mm):	91 × 76.8
		80 × 79.8
OTHERS	Winch:	2,000 lbs
	Gear Selection:	L / H / N / R / P
	Drive Mode:	2WD / 4WD
	Max. Towing Capacity:	500 kg
	Front Tire:	AT25×8-12 tubeless
	Rear Tire:	AT25×10-12 tubeless
	Loading Quantity (40' HQ):	32 units



T500

750 kg TOWING
310 mm CLEARANCE

T500		
VEHICLE	Weight (kg):	Curb: 410 / Gross: 486
	Dimensions (mm):	2370 × 1330 × 980
	Packing Dimensions (mm):	2250 × 1160 × 1130
	Ground Clearance (mm):	310
	Wheelbase (mm):	1300
	Fuel Tank Capacity (L):	20
	Braking System:	Hydraulic Disc Brake(s)
	Shock:	Hydraulic (F&R)
POWER	Max. Speed (km/h):	90
	Engine Type:	Single Cylinder, Water-Cooled
	Displacement (cc) / Type:	500 / CVT / SOHC
	Rated Power:	25 kW
	Max. Engine Speed:	7,500 rpm
OTHERS	Peak Torque:	43.3 N·m
	Winch:	2,000 lbs
	Gear Selection:	L / H / N / R
	Drive Mode:	2WD / 4WD
	Max. Towing Capacity:	750 kg
	Front Tire:	AT26×9-14 tubeless
	Rear Tire:	AT26×11-14 tubeless
	Loading Quantity (40' HQ):	20 units



T400
2WD/4WD

T400
SHAFT DRIVE

T300
2WD

T300
CHAIN DRIVE



T400 & T300

TWO ENGINE CHOICES
2WD OR 4WD OPTION

	T400	T300
VEHICLE	Weight (kg):	Curb: 351 / Gross: 368
	Dimensions (mm):	2090 × 1210 × 1170
	Packing Dimensions (mm):	1970 × 1140 × 880
	Ground Clearance (mm):	310
	Wheelbase (mm):	1360
	Fuel Tank Capacity (L):	15
	Braking System:	Hydraulic Disc Brake(s)
	Shock:	Hydraulic (F&R)
	Max. Speed (km/h):	80
		95
POWER	Engine Type:	Single Cylinder, Water-Cooled
	Displacement (cc) / Type:	390.8 / CVT / SOHC
	Max. Power:	19 kW @ 6,500–7,000 rpm
	Max. Torque:	30 N·m @ 5,000 rpm
	Compression Ratio:	10:1
	Bore × Stroke (mm):	82 × 74
		72.7 × 65.2
OTHERS	Winch:	2,000 lbs
	Gear Selection:	L / H / N / R
	Drive / Final Drive:	2WD / 4WD
	Max. Towing Capacity:	500 kg
	Front Tire:	AT25×8-12 tubeless
	Rear Tire:	AT25×10-12 tubeless
	Loading Quantity (40' HQ):	32 units
		36 units



Type: T300

Yongtu Power Technology Co., Limited

Date : 01/08/2028

Ext. : 00

EUROPEAN TYPE-APPROVAL OF AGRICULTURAL AND FORESTRY VEHICLES

(Information Folder No. T300-00)

INDEX OF INFORMATION DOCUMENT

INDEX OF CONTENT

APPENDIX	CONTENT
1	INFORMATION ON THE TYPE-APPROVAL PROCEDURE CHOSEN
2	VARIANTS AND VERSIONS MATRIX
3	INFORMATION DOCUMENT AND DRAWINGS
4	CERTIFICATE ON ACCESS TO VEHICLE ON-BOARD DIAGNOSTIC (OBD) SYSTEMS AND TO VEHICLE REPAIR AND MAINTENANCE INFORMATION
5	DECLARATION ON ANTI-TAMPERING OF POWERTRAIN AND SPEED-LIMITATION DEVICE
6	FOR VEHICLES EQUIPPED WITH (AN) ELECTRICAL/ELECTRONIC DEVICE(S) WHICH LIMIT ITS PROPULSION PERFORMANCE, DATA AND EVIDENCE TO DEMONSTRATE THAT MODIFICATION OR DISCONNECTION OF THE DEVICE OR ITS WIRING SYSTEM WILL NOT INCREASE THE PROPULSION PERFORMANCE (IF APPLICABLE)
7	STATEMENTS ON STRUCTURE INTEGRITY

3/134

T300

Yongtu Power Technology Co., Limited

Date : 01/08/2028

Ext. : 00

Appendix 1

Information

on the type-approval procedure chosen in accordance with Article 20(1) of Regulation (EU) No 167/2013 of the European Parliament and of the Council

Information folder sheet.

The undersigned: Weiyan Yang / General Manager

Company name and address of the manufacturer:

Yongtu Power Technology Co., Limited

Flat 03C3, 15F, Carnival Comm Bldg, 18 Java Road, North Point, Hong Kong, China

Name and address of the manufacturer's representative (if any):

R.C. HOLM A/S

Industrivej 18 DK-8963 Auning, Denmark

Hereby applies for type-approval procedure:

(a) step-by-step type-approval

(b) single-step type-approval

(c) mixed type-approval

Where procedures (a) or (c) are chosen, compliance with requirements as under (b) is declared for all systems, components and separate technical units.

Multi-stage type-approval chosen in accordance with Article 20(5) of Regulation (EU) No 167/2013: yes/no

Information on the vehicle(s) to be filled in, if application is for EU whole-vehicle type-approval:

1.1. Make (trade name of the manufacturer): GREEN MANTIS, YONTUL

1.2. Type: T300

1.2.1. Variant(s): 00

1.2.2. Version(s): 00/01

1.2.3. Commercial name(s) (if available): T300

1.2.4. Type-approval number(s) of the previous stage(s): Not applicable

1.3. Category, subcategory and speed index of the vehicle: T3b

3/134

Temporary Type-Approval Certificate No.: e25167/201330001*00

T300

EU T3b TYPE APPROVAL

For specified vehicle configurations

APPROVAL SCOPE

EU type approval covers the T300 configurations listed in the certificate. A matching Certificate of Conformity supports registration, subject to national requirements.

TRAIL & UTILITY

With two seats, 2WD and a towing capacity of up to 500 kg, the T300 is equipped for trail riding and practical work around a property.





T300-EV & T300

ELECTRIC OR PETROL
CHOOSE YOUR POWER

	T300-EV	T300
VEHICLE	Weight (kg):	Curb: 350 / Gross: 390
	Dimensions (mm):	2085 × 1180 × 1175
	Packing Dimensions (mm):	2250 × 1160 × 1130
	Ground Clearance (mm):	252
	Wheelbase (mm):	1360
	Fuel Tank / Battery:	72 V / 120 Ah
	Braking System:	Hydraulic Disc Brake(s)
	Shock:	Hydraulic (F&R)
	Max. Speed (km/h):	90
POWER	Engine / Motor:	72 V electric motor; 12,000 rpm max
	Displacement / Rated Power:	6 kW
	Max. Power:	12 kW
	Max. Torque / Controller:	72 V; 340 A peak
	Range (km):	80 km
	Charging / Battery Type (EV):	72 V LFP; charging heater
	Winch:	2,000 lbs
OTHERS	Gear Selection:	H / L / N / R
	Drive / Final Drive:	2WD
	Max. Towing Capacity:	500 kg
	Front Tire:	AT25×8-12 tubeless
	Rear Tire:	AT25×10-12 tubeless
	Loading Quantity (40' HQ):	36 units



T200

200 cc TRAIL POWER BEYOND THE ROAD

T200		
VEHICLE	Net / Gross Weight (kg):	224 / 240
	Dimensions (mm):	1930 × 1110 × 1300
	Seat-to-Footrest Height (mm):	530
	Ground Clearance (mm):	180 (under rear axle)
	Wheelbase (mm):	1260
	Fuel Tank Capacity (L):	10
	Braking System:	Hydraulic disc brake
	Suspension:	Front: double A-arm, 100 mm; rear: swingarm, 90 mm
POWER	Max. Speed (km/h):	60
	Engine:	JUNENG 200 cc, oil-cooled, 4-stroke, balance shaft
	Max. Power:	9.5 kW @ 7,000 rpm
	Max. Torque:	13.5 N·m @ 5,500 rpm
	Bore × Stroke (mm):	65 × 60
OTHERS	Fuel Delivery:	Carburetor PD27
	Drive System:	Chain drive / solid axle
	Transmission:	F / N / R
	Battery:	12 V / 9 Ah dry battery
	Final Drive:	O-ring chain drive 530
	Front Tire / Wheel:	23×7-10; iron wheel
	Rear Tire / Wheel:	22×10-10; iron wheel
	Loading Quantity (40' HQ):	36 units



T150

150 cc TRAIL POWER

READY TO RIDE

T150		
VEHICLE	Net / Gross Weight (kg):	138 / 148
	Dimensions (mm):	1610 × 930 × 1040
	Seat-to-Footrest Height (mm):	450
	Ground Clearance (mm):	130 (under rear axle)
	Wheelbase (mm):	1030
	Fuel Tank Capacity (L):	6.5
	Braking System:	Hydraulic disc brake
	Suspension:	Front: double A-arm, 80 mm; rear: swingarm, 65 mm
POWER	Max. Speed (km/h):	60
	Engine:	Shineray 150 cc, air/oil-cooled, 4-stroke, balance shaft
	Max. Power:	6.3 kW @ 7,500 rpm
	Max. Torque:	10 N·m @ 5,500 rpm
	Bore × Stroke (mm):	56.5 × 57.8
OTHERS	Fuel Delivery:	Carburetor PZ27
	Drive System:	Chain drive / solid axle
	Transmission:	F / N / R or 3F / N / R
	Battery:	12 V / 7 Ah dry battery
	Final Drive:	O-ring chain drive 428
	Front Tire / Wheel:	19×7-8; iron wheel
	Rear Tire / Wheel:	18×9.5-8; iron wheel
	Loading Quantity (40' HQ):	80 units



Y25

180 kg LOAD CAPACITY
READY FOR DAILY WORK

Y25		
VEHICLE	Dimensions (mm):	2040 × 770 × 1050
	Wheelbase (mm):	1390
	Curb Weight (kg):	143
	Max. Load Capacity (kg):	180
POWER	Max. Speed (km/h):	85
	Range:	80–120 km
	Motor:	6-Phase Planetary Gear Hub Motor, 72 V
	Rated / Peak Power:	5 kW / 10 kW
	Peak Torque:	385 N·m
	Peak Motor Speed:	810 rpm
	Controller:	Bus 100 A / Phase 450 A
	Battery:	60 Ah LFP (Lithium Iron Phosphate)
	Battery Dimensions (mm):	300 × 270 × 345
	Charging:	15 A, 5 h, 2000 cycles
OTHERS	Planetary Gear Ratio:	4.28:1
	Front / Rear Tires:	FR: 80/90-17; RR: 100/80-17
	Braking System:	Front & Rear Disc Brake
	Rear Shock Absorber:	Hydraulic Twin-Spring
	Climbing Angle:	≥30°
	Kinetic Energy Recovery:	YES
Loading Quantity (40' HQ):		CKD: 168 units / SKD: 105 units



Y22

HUB OR MID-DRIVE POWER YOUR WAY

Y22		
VEHICLE	Dimensions (mm):	1964 × 767 × 1260
	Wheelbase (mm):	1366
	Ground Clearance (mm):	188
	Max. Load Capacity (kg):	150
POWER 1 (LFP)	Battery:	72 V / 45 Ah LFP battery
	Motor:	Hub Motor 3000 W
	Max. Speed (km/h):	80
	Max. Range:	110 km
POWER 2 (NMC)	Battery:	72 V / 45 Ah × 2 NMC battery (Optional: 2 battery packs)
	Motor:	Mid-drive 4500 W
	Max. Speed (km/h):	80
	Max. Range:	110 km



Y21

TWO BATTERY CHOICES UP TO 180 km RANGE

Y21		
VEHICLE	Dimensions (mm):	1958 × 680 × 1113
	Wheelbase (mm):	1366
	Max. Load Capacity (kg):	150
	Ground Clearance (mm):	150
POWER 1 (LFP)	Battery:	72 V / 30 Ah LFP battery (Optional: 2 battery packs)
	Motor Power:	Hub Motor 3000 W
	Max. Speed (km/h):	80
	Max. Range:	150 km
POWER 2 (NMC)	Battery:	72 V / 40 Ah NMC battery (Optional: 2 battery packs)
	Motor Power:	Hub Motor 3000 W
	Max. Speed (km/h):	80
	Max. Range:	180 km



Y20

2.5 kW CITY POWER
UP TO 70 km RANGE

Y20		
VEHICLE	Dimensions (mm):	1880 × 740 × 1140
	Wheelbase (mm):	1300
	Ground Clearance (mm):	120
	Weight incl. Battery (kg):	115
	Max. Load Capacity (kg):	75
POWER	Battery:	72 V / 40 Ah lithium battery
	Motor Power:	2500 W
	Controller:	40 A intelligent controller
	Max. Speed (km/h):	50
	Max. Range:	70 km
	Charging Time (0–100%):	6–8 h (220 V)
OTHERS	Front / Rear Tires:	90/90-12 tubeless
	Braking System:	Front & rear linked disc brake
	Dashboard:	LCD display
	Lighting:	12 V LED



Y19

COASTAL STYLE

UP TO 70 km RANGE

Y19		
VEHICLE	Dimensions (mm):	1930 × 770 × 1150
	Wheelbase (mm):	1300
	Ground Clearance (mm):	120
	Weight incl. Battery (kg):	110
	Max. Load Capacity (kg):	75
POWER	Battery:	72 V / 40 Ah lithium battery
	Motor Power:	2200 W
	Controller:	40 A intelligent controller
	Max. Speed (km/h):	45
	Max. Range:	70 km
	Charging Time (0–100%):	6–8 h (220 V)
OTHERS	Front / Rear Tires:	90/90-12 tubeless
	Braking System:	Front & rear linked disc brake
	Dashboard:	LCD display
	Lighting:	12 V LED



Y18

BATTERY OPTIONS UP TO 60 km/h

Y18		
VEHICLE	Dimensions (mm):	1740 × 700 × 1100
	Carton Dimensions (mm):	1600 × 410 × 800
	Wheelbase (mm):	1245
	Seat Height (mm):	750
	Ground Clearance (mm):	130
	Curb Weight (kg; excl. battery):	65
	Max. Load (kg):	150
POWER	Max. Speed (km/h):	60
	Range (by battery):	Lead-acid 40 / 55 / 70 km; lithium 60–200 km
	Motor / Rated Power:	1000 W hub motor
	Battery Options:	48 / 60 / 72 V; 20–40 Ah; lead-acid / lithium
	Charger (72 V option):	72 V / 2.5–3 A
	Charging Time:	6–8 h
	Climbing Angle:	≤15°
OTHERS	Frame:	Truss-type steel tube
	Suspension:	Front: Ø27 oil-damped; rear: dual oil-damped
	Front / Rear Tires:	3.0-10 tubeless
	Brakes:	Front 200 mm disc; rear 110 mm drum
	Instrument:	Digital display
	Lighting:	LED headlight, tail light & turn signals



Y17

3 kW CITY POWER

85–100 km RANGE

Y17		
VEHICLE	Dimensions (mm):	1965 × 755 × 1240
	Wheelbase (mm):	1350
	Curb Weight (kg):	80
	Max. Load Capacity (kg):	150
POWER	Max. Speed (km/h):	75
	Range:	85–100 km
	Motor:	72 V / 3000 W
	Rated Power:	3 kW
	Battery:	72 V / 50 Ah lithium
	Charger:	Input 100–240 V / Output 72 V, 8 A
OTHERS	Charging Time (0–100%):	7–9 h
	Frame:	Truss-type steel tube
	Front Suspension:	Straight tube hydraulic shocks
	Rear Suspension:	Dual hydraulic shocks
	Front / Rear Tires:	110/80-14 tubeless
	Braking System:	Front & rear linked disc brake
	Dashboard:	TFT
	Riding Modes:	3-speed electronic shift



Y16

3 kW CITY POWER

THREE SPEED SETTINGS

Y16		
VEHICLE	Dimensions (mm):	1965 × 755 × 1240
	Wheelbase (mm):	1350
	Curb Weight (kg):	80
	Max. Load Capacity (kg):	150
POWER	Max. Speed (km/h):	75
	Range:	85–100 km
	Motor:	72 V / 3000 W
	Rated Power:	3 kW
	Battery:	72 V / 50 Ah lithium
	Charger:	Input 100–240 V / Output 72 V, 8 A
OTHERS	Charging Time (0–100%):	7–9 h
	Frame:	Truss-type steel tube
	Front Suspension:	Straight tube hydraulic shocks
	Rear Suspension:	Dual hydraulic shocks
	Front / Rear Tires:	110/80-14 tubeless
	Braking System:	Front & rear linked disc brake
	Dashboard:	TFT
	Riding Modes:	3-speed electronic shift



Y15

1000 W HUB MOTOR
UP TO 60 km/h

Y15		
VEHICLE	Dimensions (mm):	1740 × 700 × 1100
	Carton Dimensions (mm):	1600 × 400 × 850
	Wheelbase (mm):	1245
	Seat Height (mm):	750
	Ground Clearance (mm):	130
	Curb Weight (kg; excl. battery):	65
	Max. Load (kg):	150
POWER	Max. Speed (km/h):	60
	Range (by battery):	Lead-acid 40 / 55 / 70 km; lithium 60–200 km
	Motor / Rated Power:	1000 W Hub motor
	Battery Options:	48 / 60 / 72 V; 20–40 Ah; lead-acid / lithium
	Charger (72 V option):	72 V / 2.5–3 A
	Charging Time:	6–8 h
	Climbing Angle:	≤15°
OTHERS	Frame:	Truss-type steel tube
	Suspension:	Front: Ø27 oil-damped; rear: dual oil-damped
	Front / Rear Tires:	3.0-10 tubeless
	Brakes:	Front 200 mm disc; rear 110 mm drum
	Instrument:	Digital display
	Lighting:	LED headlight, tail light & turn signals



Y13

CLASSIC CITY STYLE

THREE SPEED MODES

Y13		
VEHICLE	Dimensions (mm):	1680 × 690 × 1190
	Wheelbase (mm):	1265
	Seat Height (mm):	790
	Ground Clearance (mm):	210
	Curb Weight (kg):	74 (including battery)
	Max. Load Capacity (kg):	150
POWER	Max. Speed (km/h):	65
	Range:	55 km @ 25 km/h
	Motor Type:	QS Hub Motor
	Rated Power:	2 kW
	Peak Power:	2.5 kW
	Battery:	60 V / 18.2 Ah NCM battery
	Charger Maximum Power:	160 W
	Charger Output:	67.2 V, 2 A
	Charging Time (0–100%):	7–8 h
OTHERS	Frame:	Truss-type steel tube
	Front Suspension:	Dual hydraulic shocks
	Rear Suspension:	Dual spring shocks
	Front / Rear Tires:	225/40-10
	Front Brake:	Disc brake
	Rear Brake:	Disc brake
	Display:	LCD display
	Riding Modes:	3 gears: 1st ≈25 km/h, 2nd ≈45 km/h, 3rd unrestricted
	USB Power Supply:	Yes
	Phone Holder:	Yes



T20

8.6 kW PEAK POWER

MAX SPEED 80 km/h

T20		
VEHICLE	Dimensions (mm):	1895 × 770 × 1085
	Wheelbase (mm):	1260
	Seat Height (mm):	860
	Ground Clearance (mm):	285
	Curb Weight (kg):	66
POWER	Max. Torque:	404 N·m
	Max. Speed (km/h):	80
	Range:	80 km
	Acceleration (0–50 km/h):	2.7 s
	Motor Type:	Mid-mounted PMSM, Air-cooled
	Rated Power:	4 kW
	Peak Power:	8.6 kW
	Battery:	72 V / 35 Ah
OTHERS	Charging Time (0–100%):	3.5 h
	Frame:	One-piece Forged Aluminum Alloy Frame
	Handlebar:	Aluminum Alloy
	Swingarm:	Aluminum Alloy
	Front Shock:	Inverted Ø35 mm
	Rear Shock:	Central Shock
	Front Tire:	70/100-19
	Rear Tire:	80/100-16
	Front Brake:	220 mm Disc, 2-piston Caliper
	Rear Brake:	202 mm Disc, 2-piston Caliper
	Transmission:	Gearbox + Chain Drive
	Instrument:	2 Inch Screen LCD
	Riding Modes:	ECO / SPORT
	Side Stand Cut-Off:	Yes
	Energy Regeneration:	Yes



T15-A

7 kW PEAK POWER
BUILT FOR THE TRAIL

T15		
VEHICLE	Dimensions (mm):	1790 × 690 × 1090
	Wheelbase (mm):	1250
	Seat Height (mm):	850
	Ground Clearance (mm):	275
	Curb Weight (kg):	86
POWER	Max. Torque:	404 N·m
	Max. Speed (km/h):	70
	Range:	70 km
	Motor Type:	Mid-mounted PMSM, Air-cooled
	Rated Power:	3 kW
	Peak Power:	7 kW
	Battery:	72 V / 30 Ah
OTHERS	Charging Time (0–100%):	3.5 h
	Handlebar:	High Strength Steel
	Swingarm:	High Strength Steel
	Front Shock:	Inverted, non-adjustable
	Rear Shock:	Central Shock, non-adjustable
	Front Tire:	70/100-19
	Rear Tire:	80/100-16
	Front Brake:	Hydraulic disc brake
	Rear Brake:	Hydraulic disc brake
	Transmission:	Chain Drive
	Instrument:	LCD
	Riding Modes:	ECO / SPORT



T15-B

7 kW PEAK POWER

BUILT FOR THE TRAIL

T15		
VEHICLE	Dimensions (mm):	1790 × 690 × 1090
	Wheelbase (mm):	1250
	Seat Height (mm):	850
	Ground Clearance (mm):	275
	Curb Weight (kg):	86
POWER	Max. Torque:	404 N·m
	Max. Speed (km/h):	70
	Range:	70 km
	Motor Type:	Mid-mounted PMSM, Air-cooled
	Rated Power:	3 kW
	Peak Power:	7 kW
	Battery:	72 V / 30 Ah
OTHERS	Charging Time (0–100%):	3.5 h
	Handlebar:	High Strength Steel
	Swingarm:	High Strength Steel
	Front Shock:	Inverted, non-adjustable
	Rear Shock:	Central Shock, non-adjustable
	Front Tire:	70/100-19
	Rear Tire:	80/100-16
	Front Brake:	Hydraulic disc brake
	Rear Brake:	Hydraulic disc brake
	Transmission:	Chain Drive
	Instrument:	LCD
	Riding Modes:	ECO / SPORT



T10 & T05

TWO SIZES
TWO POWER LEVELS

		T10	T05
VEHICLE	Dimensions (mm):	1640 × 700 × 1090	1570 × 700 × 1040
	Wheelbase (mm):	1085	1085
	Ground Clearance (mm):	260	220
	Curb Weight (kg):	64	62
POWER	Max. Speed (km/h):	75	60
	Range:	50 km	50 km
	Motor Type:	Mid-mounted PMSM	Mid-mounted PMSM
	Rated Voltage (V):	60	48
	Rated Power (kW):	3	2
	Battery:	60 V / 31.5 Ah lithium	48 V / 20 Ah lithium
	Charger:	60 V / 5 A	48 V / 4 A
	Charging Time (0–100%):	6–7 h	5–6 h
OTHERS	Handlebar:	High Strength Steel	High Strength Steel
	Swingarm:	High Strength Steel	High Strength Steel
	Front Shock:	Hydraulic suspension fork	Hydraulic suspension fork
	Rear Shock:	Hydraulic shock absorber	Hydraulic shock absorber
	Front Tire:	70/100-17	60/100-14
	Rear Tire:	90/100-14	80/100-12
	Front Brake:	Hydraulic disc brake	Hydraulic disc brake
	Rear Brake:	Hydraulic disc brake	Hydraulic disc brake
	Transmission:	Chain drive	Chain drive
	Instrument:	LCD	LCD